



"STARPADS" SEPARATORS FOR LISEC MACHINE

Constructive features

Materials:	Agglomerated natural cork + pvc foam
Density of cork:	180 - 210 kg/m ³
Granulometry:	1 - 2 mm
Density of foam:	100 - 125 kg/m ³
Format:	Bobbins of 18 mm x 300 mts

Technical characteristics

Hardness:	55 - 60
Tensile strength of cork:	6 - 8 kg/cm ²
Tensile strength of foam:	100 kpa (DIN 53571)
Recovery:	75%
Compression (F5):	No cracks
Elongation at brake of foam:	120% (DIN 53571)

Lisec bobbins cork+pvc	In rolls				
	Description	size	Thickness	units/bobbin	Reference
	Lisec bobbins of cork+pvc 18x3+2 (300 mts.)	18mm.x300 mts.	3+2 mm.	16.650	0510LISEC

"STARPADS" SEPARATORS FOR LENHARDT MACHINE

Constructive features

Materials:	Agglomerated natural cork + pvc foam
Density of cork:	180 - 210 kg/m ³
Granulometry:	1 - 2 mm
Density of foam:	100 - 125 kg/m ³
Liner:	Transparent film of polyethylene of 400 microns
Format:	Bobbins of 300 mts. or rolls of 41,5 mts.

Technical characteristics

Hardness:	55 - 60
Tensile strength of cork:	6 - 8 kg/cm ²
Tensile strength of foam:	100 kpa (DIN 53571)
Recovery:	75%
Compression (F5):	No Cracks
Elongation at break of foam:	120% (DIN 53571)

Lenhardt bobbins cork+pvc	In rolls				
	Description	size	Thickness	units/bobbin	Reference
	Lenhardt-Bystronic bobbins cork+pvc 18x3+2	300 mts	3+2	16.650	0510LENH
	Lenhardt Bystronic bobbins cork+pvc 18x3+2	41,5 mts	3+2	2.300	0510001



Productos de corcho. Cork products

C/ Santiago Russinyol, 14 nave C 7-9, Pol. Ind. Can Humet de Dalt
08123 Polinyà, Barcelona, Spain.
Tel. +34 93 309 77 83 · info@barnacork.com
www.bamacork.com · www.corkshopbcn.com

"STARPADS" SEPARATORS FOR AUTOMATIC PROCESSES

Constructive features

Materials:	Agglomerated natural cork + removable adhesive
Density:	240 kg/m ³
Granulometry:	1 - 2 mm
Internal side adhesive:	Acrylic
External side adhesive:	Removable Acrylic
Carrier:	non-woven
Liner:	Siliconized Paper
Format:	Rolls

Technical characteristics

Hardness:	55 - 60
Tensile strength:	> 550 kPa
Recovery (100 psi):	> 70%
Compression (100 psi):	15 - 30 %
Temperature resistance:	-20°C +100°C
Durability:	12 months to 21°C and 50% HR

Automatic processes

In rolls

Description	size	Thickness	units/bobbin	Reference
bobbins of adhesive cork 28x28x12 mm (14 mts)	28x28 mm	12 mm	500	0512058
For other measurements, formats o materials, consult.				