



"STARPADS" GREEN ADHESIVE PVC

Constructive features

Materials:	Pvc foam
Density:	350 kg/m3
Adhesive:	Removable Acrylic
Liner:	siliconized paper
Format:	Rolls

Technical characteristics

Format:	Rolls
Force to compress by 30% N/cm2	minimum 10 - SGTM 14
Service temperature °C	long term -40 to + 70
Compression (F5):	no cracks
Elongation at break of foam:	120% (DIN 53571)

Cork+pvc	In rolls				
Description	size	Thickness	Units/roll	Units/box	Reference
green adhesive pvc "Starpad" (rolls) 15x15 mm.	15x15 mm	4 mm	14.000	56.000	0515002
green adhesive pvc "Starpad" (rolls) 17,8x16,2 mm.	17,8x16,2 mm	4 mm	12.000	48.000	0515001
green adhesive pvc "Starpad" (rolls) 18x18 mm.	18x18mm	4 mm	11.000	44.000	0515003

In rolls, for other sizes, consult.

"STARPADS" SEPARATORS FOR MANUFACTURERS

Constructive features

Materials:	Agglomerated natural cork + nitrilic rubber
Density:	750 - 900 Kg/m3
Granulometry:	0,5 / 1 mm
Internal side adhesive:	Acrylic
External side adhesive:	Removable Acrylic
Carrier:	non- woven
Liner:	siliconized paper
Format:	Rolls

Technical characteristics

Hardness:	70 - 80 Shore A
Tensile strength:	2,35 Mpa
Recovery:	80%
Compression 400 psi:	20% - 30%
Temperature Resistance:	-20°C +100°C
Durability:	12 months to 21°C and 50% HR

Cork+pvc	In rolls				
Description	size	Thickness	Units/roll	Units/box	Reference
Starpad rolls for manufactures 10x10x0,5 mm	10x10 mm	0,5 mm	12.000	96.000	0512042
Starpad rolls for manufactures 12x12x0,5 mm	12x12 mm	0,5 mm	8.250	66.000	0512043
Starpad rolls for manufactures 15x15x0,5 mm	15x15 mm	0,5 mm	5.250	42.000	0512044

"STARPADS" SEPARATORS IN INDIVIDUAL BOXES

Constructive features

Materials:	Agglomerated natural cork + removable adhesive
Density:	180 - 210 kg/m ³
Granulometry:	1 - 2 mm
Internal side adhesive:	Acrylic
External side adhesive:	Removable Acrylic
Carrier:	non- woven
Liner:	siliconized paper
Format:	Sheets of 315x195 mm

Technical characteristics

Hardness:	55 - 60
Tensile strength:	6 - 8 Kg/cm ²
Recovery:	75%
Compression (F5):	No cracks
Temperature Resistance:	-20°C +100°C
Durability:	12 meses a 21°C y 50% HR

Adhesive cork in small boxes	in sheets				
	Description	size	Thickness	Units/box	Reference
	Starpad adhesive cork box 15x15x3 mm	15x15 mm	3 mm	5.460	0512015
	Starpad adhesive cork box 18x18x3 mm	18x18 mm	3 mm	3.960	0512014
	Starpad adhesive cork box 20x20x3 mm	20x20 mm	3 mm	3.200	0512011

"STARPADS" POLYETHYLENE PROTECTIVE BOBBINS

Constructive features

Materials:	Polyethylene foam of closed cell
Density:	25 kg/m ³
N° cells/inch:	i5 - 16
Internal side adhesive:	Acrylic
External side adhesive:	Removable acrylic
Carrier:	non-woven
Format:	Rolls
Cut:	Pre-punched polyethylene rolls

Technical characteristics

Resistance to the traction (DIN53571):	
Max. longitudinal force	29,5 N
Max. transverse force	22,6 N
Longitudinal elongation	90,7%
Transverse elongation	60,1%
Fuerza de compresión (DIN53577) 50%:	
25% 4° compression	322 N
50% 4° compression	920 N
70% 4° compression	2138 N

Polyethylene protective bobbins	in rolls				
	Description	size	Thickness	Units/box	Reference
	Pre-die cutting polyethylene bobbin	50 mm x 12,5 mts	10 mm	12 uds	0516001
	Pre-die cutting polyethylene bobbin	75 mm x 12,5 mts	10 mm	8 uds	0516002
	Pre-die cutting polyethylene bobbin	100 mm x12,5 mts	10 mm	6 uds	0516003